

ECOEXIT1BOX

Stanilite Single Point Economy Exit Lighting with LiFEPO4 Battery and S/CONN Wall and Ceiling Mount



Stanilite®



Component type	Emergency luminaire
Range	Single Point Economy Exit Lighting
Model	N/A
Product status	Existing

The Stanilite single point economy exit lighting range features larger terminals for faster installation, efficient lithium power and universal surface mount application.

ELECTRICAL

Operating mode	Maintained
Nominal voltage	240 V
Voltage type	AC
Max. system power	4.5 W
Viewing distance	24 m
Nominal operation time	75000 h

CONSTRUCTION

With remote switch connection	No
With remote control	No
Mounting method	Wall surface mounted / ceiling surface mounting
With pictogram	Yes
With light source	Yes
Material housing	Plastic
Colour housing	White
Material cover	Plastic, opal
IP rating	IP20

PHOTOMETRIC

Lamp type	LED exchangeable
Photometric classification (C0)	D3.2
Photometric classification	D3.2

DIMENSIONS

Height/depth	224 mm
Length	362 mm

CERTIFICATES/APPROVALS

Compliant to AS/NZS CISPR 15	Yes
Compliant to AS/NZS 2293.3:2018	Yes
Compliant to AS/NZS 60598.1:2017	Yes
Compliant to AS/NZS 60598.2.22:2005	Yes

ECOEXIT1BOX

Stanilite Single Point Economy Exit Lighting with LIFEPO4
Battery and S/CONN Wall and Ceiling Mount



Stanilite®

DIMENSIONAL DIAGRAM

100mm



224mm

362mm