

Photoelectric lighting controller

NightMatic 2000

black

EAN 4007841 550318

Article number 550318



Twilight switch

1000 W

1000 W max.
(LED-ready)



IP54



2 - 30 lux



energy saving

3 years

manufacturer's
warranty
steinel.de/garantie3y



CE



TÜV Nord
Baumuster
checked

Function description

Automatic illumination. Photo-electric lighting controller NightMatic 2000, for controlling lighting systems for building fronts, properties, shop windows etc., automatically switches light 'ON' at dusk automatically 'OFF' again at dawn.

Technical specifications

Dimensions (L x W x H)	37 x 74 x 99 mm
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	black
PU1, EAN	4007841550318
Type	Photo-cell controller
Application, place	Outdoors
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Colour	black
Colour, RAL	9005
Includes corner wall mount	No
Installation site	wall
Installation	Surface wiring, Wall
IP-rating	IP54
Ambient temperature	-20 – 50 °C
Material	Plastic

Mains power supply	230 – 240 V / 50 Hz
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	4 pcs.
Fluorescent lamps, uncorrected	500 VA
Capacitive load in µF	88 µF
Power consumption	0,8 W
Sensor Technology	Light sensor
Twilight setting	2 – 30 lx
Basic light level function	No
Main light adjustable	No
Twilight setting TEACH	Yes
Constant-lighting control	No
Interconnection	Yes
Type of interconnection	Master/master
Interconnection via	Cable

Photoelectric lighting controller

NightMatic 2000

black

EAN 4007841 550318

Article number 550318



Dimension Drawing

