






Key features

- Plain or slotted channel available.
- Channel available in both 1.5mm and 2.5mm thick.
- Supplied in 3 & 6 metre lengths.
- Back to back strut available.
- All external brackets 6mm thick.
- Manufactured from continuously hot dipped zinc coated low carbon steel strip to BS EN 10346: 2009.
- Brackets are designed to comply with BS 6946.
- Channel brackets post hot dipped galvanised to BS 729.
- Tamlex strut framework lengths can be cut to any length to suit customer requirements.


Plain Strut



Size mm	Cat. No.
41x21x1.5 x 3M	TS21P-3LG
41x21x2.5 x 3M	TS21P-3
41x21x2.5 x 6M	TS21P-6

Size mm	Cat. No.
41x41x1.5 x 3M	TS41P-3LG
41x41x2.5 x 3M	TS41P-3
41x41x2.5 x 6M	TS41P-6

Slotted Strut



Size mm	Cat. No.
41x21x1.5 x 3M	TS21S-3LG
41x21x2.5 x 3M	TS21S-3
41x21x2.5 x 6M	TS21S-6

Size mm	Cat. No.
41x41x1.5 x 3M	TS41S-3LG
41x41x2.5 x 3M	TS41S-3
41x41x2.5 x 6M	TS41S-6

Tamlex can also offer a cut to length service for the Strut Framework System.

Did you know


Tamlex Strut Framework System also comes as a light gauge section, Ref. LG following the part number.

Back to Back

TS21P-3B2B





TS41P-3B2B



Size mm	Cat. No.
41x21x2.5 x 3M	TS21P-3B2B
41x21x1.5 x 3M	TS21P-3B2BLG

Size mm	Cat. No.
41x41x2.5 x 3M	TS41P-3B2B
41x41x1.5 x 3M	TS41P-3B2BLG
41x41x2.5 x 6M	TS41P-6B2B

Couplers





Internal couplers supplied with fixing screws

Size mm	Cat. No.
41 x 21 INTERNAL	TA105-21
41 x 41 INTERNAL	TA105-41

Size mm	Cat. No.
41 x 21 EXTERNAL	TB201
41 x 41 EXTERNAL	TB202

Support Brackets



Size mm	Cat. No.
2 HOLE 40 x 40	TB140

Size mm	Cat. No.
3 HOLE 100 x 40	TB142

Size mm	Cat. No.
4 HOLE 100 x 80	TB144

Size mm	Cat. No.
4 HOLE GUSSET	TB145

