Tamlite Lighting
Data Sheet

Order Code: IKN300MBNWM3

IKON Recessed downlight 28W - 4000K - Medium beam - Fixed output - Emergency



IP20 | IK04 | 5 YR

Features

- Efficacy - 107 lm/W
- Suitable for general and accent areas or retail applications
- Anodised polished aluminium reflector
- Recessed downlight with high output reflector
- CRI: Ra>80

Construction

- Die-cast aluminium body
- White trim (RAL 9016)
- Remote driver

Installation Notes

Recessed into plasterboard or exposed grid ceiling via spring clips

To Specify

IKON Recessed downlight 28W - 4000K - Medium beam - Fixed output - Emergency as per Tamlite IKON range.

Technical Data

General

Luminaire Wattage (W)	28
Operating Temperature (ta °C)	5° - 25°

Light Output

Lumens (lm)	3000
Efficacy (lm/W)	107
Beam Angle (FWHM°)	43

Life

L90 Lifetime (HRS)	50000
L80 Lifetime (HRS)	50000
L70 Lifetime (HRS)	50000

Electrical

Rated Input Current (A)	0.14
Power Factor (pf)	0.95
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	23.5
Surge Protection (kV)	1
Total Harmonic Distortion (THD)	<20%
Output LF Ripple	±4%
Conductor Size (mm)	0.5 - 2.5
Terminal Type	4-pole grip-wire

LED

CCT (K)	4000
CRI	80
Macadam Elipses	<3

Driver

Driver Current (mA)	730
Forward Voltage (V)	33
Driver Lifetime (HRS)	50000

Emergency

Emergency Lumen Operating	270
Emergency Wattage (W)	3


Tamlite Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: technical@tamlite.co.uk
W: www.tamlitelighting.co.uk


Generated on: 15/08/2022 11:51am
Produced by Tamlite Lighting

Tamlite Lighting
Data Sheet

Photometrics



Dimensions



Tamlite Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: technical@tamlite.co.uk
W: www.tamlitelighting.co.uk

Generated on: 15/08/2022 11:51am
Produced by Tamlite Lighting