Tamlite Lighting
Data Sheet

Order Code: MBL123220NW

MODLED Recessed module 16W - 4000K - Fixed output

IP44 | IK04 | 5 YR

Features

- Efficacy - 116 lm/W
- Suitable for use in offices, schools and universities and general circulation
- Modular dimensions allow easy install in most exposed T-bar ceilings
- More consistent and uniform appearance than traditional edge-lit panels
- CRI: Ra>80

Construction

- Extruded aluminium body finished in white (RAL 9010)
- Opal PMMA diffuser
- Integral driver
- Supplied as standard with neutral white (4000K) LED

Installation Notes

Recessed into exposed T-Bar ceiling with connection to remote driver. (surface fix via Tamlite SB accessory)

To Specify

MODLED Recessed module 16W - 4000K - Fixed output as per Tamlite MODLED range.

Technical Data

General

Luminaire Wattage (W)	19
Weight (kg)	2.17
Operating Temperature (ta °C)	0° - 25°

Light Output

Lumens (lm)	2200
Efficacy (lm/W)	116
Beam Angle (FWHM°)	91

Life

L90 Lifetime (HRS)	46000
L80 Lifetime (HRS)	54000
L70 Lifetime (HRS)	54000

Electrical

Rated Input Current (A)	0.08
Power Factor (pf)	0.98
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	4.4
Surge Protection (kV)	1
Total Harmonic Distortion (THD)	<20%
Output LF Ripple	±4%
Conductor Size (mm)	0.75 - 2.5
Terminal Type	3-pole grip-wire

LED

CCT (K)	4000
CRI	80
Macadam Elipses	<3

Driver

Driver Current (mA)	420
Driver Lifetime (HRS)	50000


Tamlite Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: technical@tamlite.co.uk
W: www.tamlitelighting.co.uk


Generated on: 16/08/2022 10:33am
Produced by Tamlite Lighting

Tamlite Lighting
Data Sheet

Photometrics



Dimensions



Tamlite Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: technical@tamlite.co.uk
W: www.tamlitelighting.co.uk