



TSB2/65 SCREEDBOX

Specifications

- Floor box manufactured from galvanised steel
- 25 & 20mm knockouts to accept flexible conduit
- Frame & lid moulded from high impact polycarbonate
- Galvanised lid insert for strength
- Easy grip recessed lifting handle
- Compact design 266 x 212mm floor cut-out
- Designed to accept 2 accessory plates
- Large range of accessory plates
- Special plates available to order
- Clean earthed sockets available

Dimensions


Floor Cut Out:	266 x 212mm
Floor Box Depth:	65mm
Plug Top Clearance*:	20mm
Overall Frame & Lid:	272 x 223mm
Frame Lid Recess:	6mm
Accessories Plates:	185 x 89mm

* Accessory Plates STO286, STO286/IFM, STO287, STO287/IFM & STO291/RCD are not suitable for floorboxes below 80mm depth due to plug top clearance.


TSB2/65 Accessory Plates




STO283
Blank Plate



STO284
RJ45/LJ6C Plate



* **STO286**
2x 1 Gang
Accessory Plate




* **STO287**
Standard Twin
Accessory Plate




STO288
Alpha Snap Plate



STO289
6x RJ45/LJ6C
Data Plate



STO291
Twin Switched
Sockets




STO295
Triple Sockets




* **STO291/RCD**
Twin RCD
Protected Sockets



STO294
2x Euro 50x50mm
Plate




* **STO287/FM**
Flush Standard
Twin Plate




* **STO286/IFM**
Flush Standard
single Plate



STO284/W
4x RJ45/LJ6C
Wave Plate



STO291/NSS
2x Non-Standard
Sockets



STO291/5A
2x 5 Amp Sockets