



Main

Commercial Status	Commercialised
Range	TeSys
Product name	TeSys U
Device short name	LU2B
Product or component type	Reversing power base
Poles description	3P
Suitability for isolation	Yes
[I _{th}] conventional free air thermal current	12 A
Utilisation category	AC-41 AC-43 AC-44
[U _c] control circuit voltage	110...240 V AC 50/60 Hz 110...220 V DC

Complementary

Auxiliary contact composition	2 NO
Auxiliary contacts type	Type mirror contact (1 NC) state of the power conforming to draft IEC 60947-1 Type linked contacts (1 NO + 1 NC) conforming to IEC 60947-4-1
[U _e] rated operational voltage	690 V 500 V 440 V 230 V
Network frequency	40...60 Hz
[I _e] rated operational current	9 A at 690 V 12 A at 500 V 12 A at ≤ 440 V
[I _{cs}] rated service breaking capacity	50 kA 440 V 50 kA 230 V 4 kA 690 V 10 kA 500 V
Control circuit voltage limits	88...264 V 110...240 V AC in operation 88...242 V 110...220 V DC in operation 55 V 110...240 V AC drop-out 55 V 110...220 V DC drop-out
Typical current consumption	35 mA at 110...240 V AC I _{rms} sealed 35 mA at 110...220 V DC I _{rms} sealed 280 mA at 110...240 V AC I _{max} while closing 280 mA at 110...220 V DC I _{max} while closing
Duration of inrush phase	15 ms for DC network 25 ms for AC network 50/60 Hz
Safety reliability level	20000000 cycles 1369863 cycles
Operating time	50 ms closing for control circuit 75 ms without change of direction for power circuit 35 ms opening for control circuit 150 ms with change of direction for power circuit
Mechanical durability	15000000 cycles
Operating rate	60 cyc/mn
[U _i] rated insulation voltage	600 V conforming to CSA C22.2 No 14 690 V conforming to IEC 60947-1 3 600 V conforming to UL 508
[U _{imp}] rated impulse withstand voltage	6 kV conforming to IEC 60947-6-2

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Safe separation of circuit	400 V SELV between the control or auxiliary circuit and the main circuit conforming to IEC 60947-1 appendix N 400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1 appendix N
Connections - terminals	Power circuit : screw clamp terminals 2 cable 1.5...6 mm ² - cable stiffness: flexible - without cable end Power circuit : screw clamp terminals 2 cable 1...6 mm ² - cable stiffness: rigid - without cable end Power circuit : screw clamp terminals 2 cable 1...6 mm ² - cable stiffness: flexible - with cable end Power circuit : screw clamp terminals 1 cable 2.5...10 mm ² - cable stiffness: flexible - without cable end Power circuit : screw clamp terminals 1 cable 1...6 mm ² - cable stiffness: flexible - with cable end Power circuit : screw clamp terminals 1 cable 1...10 mm ² - cable stiffness: rigid - without cable end Control circuit : screw clamp terminals 2 cable 0.75...1.5 mm ² - cable stiffness: rigid - without cable end Control circuit : screw clamp terminals 2 cable 0.75...1.5 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 2 cable 0.34...1.5 mm ² - cable stiffness: flexible - with cable end Control circuit : screw clamp terminals 1 cable 0.75...1.5 mm ² - cable stiffness: rigid - without cable end Control circuit : screw clamp terminals 1 cable 0.75...1.5 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 1 cable 0.34...1.5 mm ² - cable stiffness: flexible - with cable end
Tightening torque	Power circuit : 1.9...2.5 N.m - with screwdriver 6 mm Philips No 2 Power circuit : 1.9...2.5 N.m - with screwdriver 6 mm flat Control circuit : 0.8...1.2 N.m - with screwdriver 5 mm Philips no 1 Control circuit : 0.8...1.2 N.m - with screwdriver 5 mm flat
Width	45 mm
Height	224 mm
Depth	126 mm
Product weight	1.27 kg

Environment

Heat dissipation	1.7 W for control circuit with LUCM 2 W for control circuit with LUCA, LUCB, LUCC, LUCD
Immunity to microbreaks	3 ms
Immunity to voltage dips	70 % 500 ms conforming to IEC 61000-4-11
Product certifications	ABS ASEFA ATEX BV CCC CSA DNV GL GOST LROS (Lloyds register of shipping) UL
Standards	CSA C22.2 No 14 type E IEC 60947-6-2 EN 60947-6-2 UL 508 type E with phase barrier
IP degree of protection	IP40 front panel outside connection zone conforming to IEC 60947-1 IP20 other faces conforming to IEC 60947-1 IP20 front panel and wired terminals conforming to IEC 60947-1
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-25...70 °C with LUCA, LUCB, LUCC, LUCD -25...60 °C with LUCM
Ambient air temperature for storage	-40...85 °C
Fire resistance	650 °C conforming to IEC 60695-2-12 960 °C parts supporting live components conforming to IEC 60695-2-12
Operating altitude	2000 m
Shock resistance	15 gn power poles closed conforming to IEC 60068-2-27 10 gn power poles open conforming to IEC 60068-2-27
Vibration resistance	4 gn 5...300 Hz power poles closed conforming to IEC 60068-2-27 2 gn 5...300 Hz power poles open conforming to IEC 60068-2-27

Resistance to electrostatic discharge	8 kV level 4 on contact conforming to IEC 61000-4-2 8 kV level 3 in open air conforming to IEC 61000-4-2
Resistance to radiated fields	10 V/m 3 conforming to IEC 61000-4-3
Resistance to fast transients	4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4 2 kV class 3 serial link conforming to IEC 61000-4-4
Non-dissipating shock wave	2 kV common mode conforming to IEC 60947-6-2 1 kV serial mode conforming to IEC 60947-6-2
Immunity to radioelectric fields	10 V conforming to IEC 61000-4-6