

Price\*: 565.74 GBP



## Main

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Range                     | Thalassa                                                      |
| Product name              | Thalassa PLM                                                  |
| Device short name         | PLM                                                           |
| Device application        | Multi-purpose                                                 |
| Product or component-type | Compact enclosure                                             |
| Enclosure nominal-height  | 1056 mm                                                       |
| Enclosure nominal width   | 852 mm                                                        |
| Enclosure nominal depth   | 350 mm                                                        |
| Enclosure mounting        | Wall mounted                                                  |
| Device composition        | Lock 1<br>Door 1<br>Body 1                                    |
| Body type                 | Built-in canopy<br>One piece moulded with notches in the rear |
| Door type                 | Transparent                                                   |
| Lock type                 | 4 points lock, handle with 5 mm double bar insert             |

## Complementary

|                             |                                                                  |
|-----------------------------|------------------------------------------------------------------|
| Number of locks             | 1                                                                |
| Mounting plate description  | Without mounting plate                                           |
| Accessibility for operation | Front                                                            |
| Removable parts             | Door by hinges                                                   |
| Material                    | Polyester reinforced with fibreglass body<br>Tempered glass door |
| Colour                      | Grey RAL 7035                                                    |
| Standards                   | NEMA classification 4X<br>NEMA classification 13<br>IEC 62208    |
| Product certifications      | UL                                                               |

## Environment

|                                     |                  |
|-------------------------------------|------------------|
| IP degree of protection             | IP66 IEC 60529   |
| IK degree of protection             | IK08 IEC 62262   |
| Fire resistance                     | 960 °C IEC 62208 |
| Ambient air temperature for storage | -35...90 °C      |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. \*Prices are indicative

## Offer Sustainability

|                                  |                                                                                                                                                                                                                        |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                                                                                                                                                  |
| RoHS (date code: YYWW)           | Compliant - since 1511 - Schneider Electric declaration of conformity  <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                                                                                                                                                      |
| Product environmental profile    | Available                                                                                                                                                                                                              |
| Product end of life instructions | Need no specific recycling operations                                                                                                                                                                                  |

Product Life Status : **Commercialised**