



## Main

|                             |                                                   |
|-----------------------------|---------------------------------------------------|
| Range of product            | Spacial S3D                                       |
| Application                 | Multi-purpose                                     |
| Category                    | Compact enclosure                                 |
| Enclosure nominal height    | 1200 mm                                           |
| Enclosure nominal width     | 1000 mm                                           |
| Enclosure nominal depth     | 300 mm                                            |
| Door type                   | Plain                                             |
| Mounting plate description  | Without mounting plate                            |
| Type of gland plate         | Standard                                          |
| Installation accessory type | Wall-mounting                                     |
| Device composition          | Lock 1<br>Door 1<br>Cable gland plate 2<br>Body 1 |

## Complementary

|                             |                                                                      |
|-----------------------------|----------------------------------------------------------------------|
| Body type                   | Gutter-shaped front rail double sheet thickness<br>Single piece body |
| Number of doors             | 1 front face                                                         |
| Door opening                | Reversible 120 °                                                     |
| Lock type                   | 3 points lock, 3 mm double-bar                                       |
| Accessibility for operation | Front                                                                |
| Removable parts             | Cable gland plate by screws<br>Door by hinges                        |
| Material                    | Steel                                                                |
| Surface finish              | Epoxy-polyester powder                                               |
| Colour                      | Grey RAL 7035                                                        |
| Standards                   | IEC 62208                                                            |
| Product certifications      | BV<br>CUL<br>DNV<br>GL<br>LR<br>UL                                   |

## Environment

|                         |                              |
|-------------------------|------------------------------|
| IP degree of protection | IP66 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

## Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS                             | Compliant - since 0940 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations                                                 |