



Main

| | |
|-----------------------------|---|
| Commercial Status | Commercialised |
| Range of product | Spacial S3D |
| Application | Multi-purpose |
| Category | Compact enclosure |
| Enclosure nominal height | 500 mm |
| Enclosure nominal width | 400 mm |
| Enclosure nominal depth | 200 mm |
| Door type | Glazed |
| Mounting plate description | Without mounting plate |
| Type of gland plate | Standard |
| Installation accessory type | Wall-mounting |
| Device composition | Cable gland plate 1 Lock 1 Door 1 Body 1 |

Complementary

| | |
|-----------------------------|--|
| Body type | Gutter-shaped front rail double sheet thickness Single piece body |
| Number of doors | 1 front face |
| Door opening | Reversible 120 ° |
| Lock type | 3 mm double-bar lock |
| Accessibility for operation | Front |
| Removable parts | Cable gland plate by screws Door by hinges |
| Material | Steel and security glass for door Steel for body |
| Surface finish | Epoxy-polyester powder |
| Colour | Grey RAL 7035 |
| Standards | IEC 62208 |
| Product certifications | BV CUL DNV GL LR UL |

Environment

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP66 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to IEC 62262 |

RoHS compliance

| | |
|--------------------------------|-----------|
| RoHS EUR status | Compliant |
| RoHS EUR conformity date(YYWW) | 0940 |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|