## NSYTBP24198T

# PC box IP66 IK08 RAL7035 Int.H225W175D80 Ext.H241W194D87 Transp.cover H20



### Main

Commercial Status	Commercialised
Range	Thalassa TBP
Device application	Multi-purpose
Category	Industrial box
Height	241 mm
Width	194 mm
Depth	87 mm
Internal height	225 mm
Internal width	175 mm
Internal depth	80 mm
Enclosure mounting	Wall mounted
Device composition	4 x cover screw
	1 x cover
	1 x body
Body type	One piece moulded
Type of front cover	Low transparent cover
Cover fixing	Plastic screws
Lock type	Outside sealed area: flat screwdriver captive screw
Removable parts	Cover, by captive screws

#### Complementary

Material	Polycarbonate	
Colour	Transparent Grey ( RAL 7035 )	
Standards	IEC 62208 UL 508 A	
Product certifications	DEMKO SEMKO TÜV UL	
IP degree of protection	IP66conforming to NEMA 4.4X	
IK degree of protection	IK08conforming to IEC 62262	
Fire resistance	960 °C	
Ambient air temperature for storage	-1560 °C	
Operating temperature	-2580 °C	

#### RoHS compliance

RoHS EUR status	Compliant	_ c
RoHS EUR conformity date(YYWW)	0940	

#### Contractual warranty

Dariad	10 months	
Period	10 MONUS	