

# NSYTBS19168T

ABS box IP66 IK07 RAL7035  
Int.H175W150D80 Ext.H193W164D87  
Transp.cover H20



## Main

|                     |                                                     |
|---------------------|-----------------------------------------------------|
| Commercial Status   | Commercialised                                      |
| Range               | Thalassa TBS                                        |
| Device application  | Multi-purpose                                       |
| Category            | Industrial box                                      |
| Height              | 192 mm                                              |
| Width               | 164 mm                                              |
| Depth               | 87 mm                                               |
| Internal height     | 175 mm                                              |
| Internal width      | 150 mm                                              |
| Internal depth      | 80 mm                                               |
| Enclosure mounting  | Wall mounted                                        |
| Device composition  | 4 x cover screw<br>1 x cover<br>1 x body            |
| Body type           | One piece moulded                                   |
| Type of front cover | Low transparent cover                               |
| Cover fixing        | Plastic screws                                      |
| Lock type           | Outside sealed area: flat screwdriver captive screw |
| Removable parts     | Cover, by captive screws                            |

## Complementary

|                                     |                                    |
|-------------------------------------|------------------------------------|
| Material                            | ABS                                |
| Colour                              | Transparent<br>Grey ( RAL 7035 )   |
| Standards                           | IEC 62208                          |
| Product certifications              | DEMKO<br>SEMKO<br>TÜV              |
| IP degree of protection             | IP66conforming to NEMA 4.4X        |
| IK degree of protection             | IK07conforming to IEC 62262        |
| Fire resistance                     | 650 °Cconforming to IEC 60695-2-11 |
| Ambient air temperature for storage | -15...40 °C                        |
| Operating temperature               | -25...60 °C                        |

## RoHS compliance

|                                |           |
|--------------------------------|-----------|
| RoHS EUR status                | Compliant |
| RoHS EUR conformity date(YYWW) | 0940      |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|