Product data sheet Characteristics

NSYTBS342916H

ABS box IP66 IK07 RAL7035 Int.H325W275D160 Ext.H341W291D168 Opaque cover H60



Main

| Commercial Status | Commercialised |
|---------------------|---|
| Range | Thalassa TBS |
| Device application | Multi-purpose |
| Category | Industrial box |
| Height | 341 mm |
| Width | 291 mm |
| Depth | 168 mm |
| Internal height | 325 mm |
| Internal width | 275 mm |
| Internal depth | 160 mm |
| Enclosure mounting | Wall mounted |
| Device composition | 4 x cover screw 1 x cover 1 x body |
| Body type | One piece moulded |
| Type of front cover | High plain cover |
| Cover fixing | Plastic screws |
| Lock type | Outside sealed area: flat screwdriver captive screw |
| Removable parts | Cover, by captive screws |
| | |

Complementary

| Material | ABS | | |
|-------------------------------------|------------------------------------|--|--|
| Colour | Grey (RAL 7035) | | |
| Standards | IEC 62208 | | |
| Product certifications | DEMKO SEMKO TÜV | | |
| IP degree of protection | IP66conforming to NEMA 4.4X | | |
| IK degree of protection | IK07conforming to IEC 62262 | | |
| Fire resistance | 650 °Cconforming to IEC 60695-2-11 | | |
| Ambient air temperature for storage | -1540 °C | | |
| Operating temperature | -2560 °C | | |

RoHS compliance

| RoHS EUR status | Compliant |
|--------------------------------|-----------|
| RoHS EUR conformity date(YYWW) | 0940 |

Contractual warrant

| Contractual warranty | | | | |
|----------------------|-----------|--|--|--|
| Period | 18 months | | | |