



## Main

Commercial Status	Commercialised
Range of product	Zelio Relay
Product or component type	Socket
Contact terminal arrangement	Separate
Product compatibility	Plug-in relay RXM (3 C/O)
Shape of pin	Flat
Device short name	RXZ
Sale per indivisible quantity	10

## Complementary

[Ith] conventional free air thermal current	5 A , with bus jumper 10 A
[Ue] rated operational voltage	< 250 V
Tightening torque	<= 1 N.m (M3 screw(s))
Fixing mode	Clip-on By screw
Marking	CE
Width	27 mm
Product weight	0.066 kg

## Environment

Connections - terminals	Connector, solid cable without cable end 2 x 0.5...2 x 1.5 mm <sup>2</sup> /AWG20...AWG16 Connector, solid cable without cable end 1 x 0.5...1 x 2.5 mm <sup>2</sup> /AWG20...AWG14 Connector, flexible cable with cable end 2 x 0.25...2 x 1 mm <sup>2</sup> /AWG22...AWG17 Connector, flexible cable with cable end 1 x 0.25...1 x 2.5 mm <sup>2</sup> /AWG22...AWG14
Standards	IEC 61984
Product certifications	CSA UL
Ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-40...55 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V