Product data sheet
Characteristics

VCFN32GE
enclosed case switch-disconnector Vario VCFN - 3 poles - 25 A

Main

Commercial Status	Commercialised
Range of product	TeSys VARIO
Device short name	Enclosed switch disconnector
Product or component type	Enclosed switch disconnector
Performance level	Standard
Switch function	Emergency stop
Poles description	3P
Network type	AC
[Ithe] conventional enclosed thermal current	25 A
Suitability for isolation	Yes

Complementary

Handle colour	Red
Handle front plate colour	Yellow
Rotary handle padlocking	Without
Network frequency	50/60 Hz
Control type	Rotary handle
[Ue] rated operational voltage	690 V AC
[Uimp] rated impulse withstand voltage	8 kV
Rated operational power in W	11 kW at 400 V AC-23
Provision for padlocking	Padlockable either by 1 (Ø 8 mm shank) or by 3 padlocks (Ø 6 mm shank)
Handle front plate dimension	60 x 60 mm
Height	131 mm
Width	82.5 mm
Depth	106 mm
Product weight	0.512 kg

Environment

Standards	IEC 60947-4-1
Product certifications	CSA GL UL
Protective treatment	TC
IP degree of protection	IP55 with protection shrouds conforming to IEC 60529
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60595-2-1

RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(YYWW)	0738

Contractual warranty

Period	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.