

Part No.	Conductor Size mm <sup>2</sup>	Stud mm	Length L	Width W	Inside Dia D	Hole Dia d $\phi$
T50-6	50	6	37.0	17.4	9.5	6.3
T50-8	50	8	37.0	17.4	9.5	8.3
T50-10	50	10	42.5	17.4	9.5	10.3
T50-12	50	12	42.5	17.4	9.5	12.8
T50-14	50	14	42.5	20.3	9.5	14.8
T50-16	50	16	52.8	23.2	9.5	16.5
T50-BL	50	-	42.5	17.4	9.5	-
T70-6	70	6	40.5	20.9	11.5	6.3
T70-8	70	8	40.5	20.9	11.5	8.2
T70-10	70	10	46.0	20.9	11.5	10.2
T70-12	70	12	46.0	20.9	11.5	12.7
T70-14	70	14	55.0	20.9	11.5	14.8
T70-16	70	16	55.0	20.9	11.5	16.3
T70-20	70	20	71.9	30.0	11.5	20.9
T70-BL	70	-	50.0	20.9	11.5	-
T95-6	95	6	49.5	24.3	13.5	6.3
T95-8	95	8	49.5	24.3	13.5	8.3
T95-10	95	10	49.5	24.3	13.5	10.3
T95-12	95	12	49.5	24.3	13.5	12.7
T95-14	95	14	56.0	24.3	13.5	14.8
T95-16	95	16	56.0	24.3	13.5	16.3
T95-20	95	20	73.6	30.0	13.5	20.9
T95-BL	95	-	56.0	24.3	13.5	-
T120-8	120	8	55.5	27.3	15.0	8.3
T120-10	120	10	55.5	27.3	15.0	10.3
T120-12	120	12	55.5	27.3	15.0	12.7
T120-14	120	14	55.5	27.3	15.0	14.8
T120-16	120	16	60.0	27.3	15.0	16.3
T120-20	120	20	76.6	30.0	15.0	20.9
T120-BL	120	-	55.5	27.3	15.0	-
T150-8	150	8	61.0	30.2	16.5	8.3
T150-10	150	10	61.0	30.2	16.5	10.2
T150-12	150	12	61.0	30.2	16.5	12.7
T150-14	150	14	61.0	30.2	16.5	14.7
T150-16	150	16	65.0	30.2	16.5	16.2
T150-20	150	20	65.0	30.2	16.5	20.8
T150-BL	150	-	65.0	30.2	16.5	-
T185-10	185	10	66.5	33.3	18.5	10.3
T185-12	185	12	68.0	33.3	18.5	12.9
T185-14	185	14	68.0	33.3	18.5	14.7
T185-16	185	16	70.0	33.3	18.5	16.5
T185-20	185	20	70.0	33.3	18.5	20.9
T185-BL	185	-	70.0	33.3	18.5	-
T240-10	240	10	88.0	37.7	21.0	10.3
T240-12	240	12	88.0	37.7	21.0	12.7
T240-14	240	14	88.0	37.7	21.0	14.7
T240-16	240	16	88.0	37.7	21.0	16.4
T240-20	240	20	88.0	37.7	21.0	20.9
T240-BL	240	-	88.0	37.7	21.0	-
T300-10	300	10	97.0	41.0	23.0	10.3
T300-12	300	12	97.0	41.0	23.0	12.7
T300-14	300	14	97.0	41.0	23.0	14.7
T300-16	300	16	97.0	41.0	23.0	16.4
T300-20	300	20	97.0	41.0	23.0	20.9
T300-BL	300	-	97.0	41.0	23.0	-