LED100FLWHP

8.5W LED Compact Floodlight Single Flood – White



Features & Benefits

- 8.5W Powerful LED compact twin floodight.
- 1000 lumen bright white light.
- Pan and tilt light aiming adjustment (per head).
- Opal Diffuser for a even light distribution.
- Rear & bottom cable entry.
- Full polycarbonate lightweight housing.
- Back box or wall mountable.
- New integrated Samsung SMD chipsets for added reliability and efficient heat dissipation.
- IP55 Weatherproof rating.

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to 50°C
Ingress Protection Rating	IP55
Wattage	8.5
Beam Angle	98° x 98°
Pan & Tilt Adjustment	Pan Left 40°, Pan Right 40°
Energy Efficiency	Class D
Energy Usage	8.5KwH/1000H

Data sheet
LED100FLWHP

Light / LED Lighting

Lumen output (lm)	1000
Colour Temperature (K)	4000
LED Type	SMD (Integrated)
Mounting Hole Centres (mm)	60
Multiple Unit Support	Yes
Cable Entry(s)	Bottom Entry (Knockouts), Back Entry

General

Weight (g)	230
Height (mm)	160
Width (mm)	80
Depth (mm)	50
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings, Setting Knob
EAN Number	5012483015858
Guarantee Period	3 Years
Trade Tariff Commodity Code	9405114090

Data sheet
LED100FLWHP

Light / LED Lighting

Line Diagrams

