
Data sheet

Light / PIR Presence Detectors

PDWM1500 – 120° PIR Presence Detector, Wall Mount

Product Image & Line Diagram





Technical Data

General	
Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Wall only – Surface or recessed
Min Depth of Wall Box	16mm, Single gang back box or pattress
Class Protection	Class 2
Number of Channels	1
Weatherproof Rating	IP55
Operating Temperature	0°C to +40°C
Accessories (Included)	Instructions, Fittings, Cable clamps, Wiring cover
Switch Rating	1500W Filament/Incandescent/Fluorescent/Low Energy, 420W LED, 250W Fan
Accessories (Optional)	None
Dimensions	Height 86mm, Width 86mm, Depth 50mm
Weight	102g
EAN	5012483011867
Designed In Accordance To	BS EN 60669-2-1 Includes updates & amendments.
Guarantee Period	3 Years
PIR Sensor	
Detection Angle	200°
Light ON Time	1 to 30 minutes, User adjustable
Slave Terminal	Yes
Detection Range	10 meters, Fixed
Permanent ON Facility	Yes, Pulse
Dusk Until Dawn Mode	No
Lux Level	5 – 1000, User adjustable
Construction;	
PIR	Polycarbonate

Timeguard Ltd reserves the right to withdraw, improve or modify any design without prior notification. Timeguard Ltd cannot be held responsible for the incorrect application of any product.
Additional information can be found at: www.timeguard.com