

## OWPIR360S OWPIR360SBK



### Cleaning Guide:

Spraying cleaning products on to electrical products is not recommended. It is important to ensure that switches are turned off before cleaning. Do not use any cleaning sprays - only wipe down with damp cloth or rub with dry cloth. (Do not use an abrasive cloth as it may scratch the plastic). Do not use harsh chemical cleaners as these can break down the plastic and cause it to crack.





## Arctic Owl Infrared Motion Sensor Indoor 360° Small

- Sensor uses Passive Infrared Technology.
- Manual override for greater convenience.
- 360 degree detection with range of 3m radius at a height of 2.4m - 4m.
- "ON" time between 10 seconds and 7 minutes - between sensing trigger.
- Suitable for loop in / loop out applications in ceilings.
- Easy mounting and adjustment.
- Parallel connections with multiple fittings.
- Rated Load: 800W Max and 400W for fluoro energy saving lamps.
- 40mm cut out.
- Colours available: White or Black.
- Depth into ceiling 36mm.

### Specifications

<b>Detection Range:</b>	360°
<b>Detection Distance:</b>	3m radius max (<24°C)
<b>Time-Delay / 'Switch On' Duration:</b>	Min. 10sec±3sec Max. 7min±2min
<b>Installing Height:</b>	2.2m - 4m
<b>Power Consumption:</b>	<0.9W
<b>Power Sourcing:</b>	220V/AC-240V/AC
<b>Power Frequency:</b>	50/60Hz
<b>Working Temperature:</b>	-20 > +40°C
<b>Ambient Light:</b>	<10-2000LUX (Adjustable)
<b>Rated Load:</b>	800W (incandescent lamp) 400W (energy-saving lamp)
<b>Working Humidity:</b>	<93%RH
<b>Detection Motion Speed:</b>	0.6 - 1.5m/s



Catalogue Number	Description
OWPIR360S	Infrared Motion Sensor, Indoor 360°, Small
OWPIR360SBK	Infrared Motion Sensor, Indoor 360°, Small, Black

**Certification Number:**  
GMA-508473

**GSM Electrical (Australia) Pty Ltd**  
Level 2, 142-144 Fullarton Road, Rose Park SA 5067  
P: 1300 301 838 F: 1300 301 778 E: service@gsme.com.au  
[www.gsme.com.au](http://www.gsme.com.au)



Data Specification Sheet  
February 2021