



POWER SENSE SWITCH

Provides automatic on/off control of a fan from an appliance when current is detected, ie: clothes dryer, range hood booster fan. LED lights indicate when load is activated. 220-240V, single phase, 50Hz.

PART NO.	LOAD SENSE ON	LOAD SENSE OFF	MAX. FAN OUTPUT	ENCLOSURE SIZE (W X H X D) MM
VZ-ISNSE	2.0A to 15A	1.5A	5A	153 x 110 x 60
VZ-ISNSE-LC	0.5A to 2.0A	0.35A	5A	153 x 110 x 60



RUN-ON TIMER

DIRECT WIRED

220-240V, single-phase, 50Hz. Designed to permit the supply of electricity to motors so they can continue to operate for a predetermined time. Can be mounted within equipment or enclosure. Size: 32W x 13H x 17D

PART NO.	START DELAY	RUN-ON TIMER	AMPS	TO SUIT FAN SELECTED
VZ24C	0 to 150 sec	Up to 24 min (1.5 min increments)	0.075 -1.25	Domestique, Silent Design, Silent, HCM, Stylvent, ProVent, Rapid Response, Ezifit Thru Wall, Ezifit In-Wall, Ezifit Thru Roof, Vogue/Ring Plate
VZ6	50 sec	6 min Fixed		
VZ12	50 sec	12 min Fixed		



RUN-ON TIMER

DIRECT WIRED SUPPLY WITH PLUG-IN OUTLET. SINGLE SWITCH INPUT

220-240V, single-phase, 50Hz. Fan with 3-pin plug and lead connects directly. Mains connection is wired directly into the terminals of the run-on timer; no need for 4-pin GPO.

PART NO.	RUN-ON TIME	MAX. AMPS	TO SUIT FAN SELECTED
VZ2-10TS	2-10 min	5.0	Domestique, Silent Design, Silent, HCM, Stylvent, ProVent, Rapid Response, Ezifit Thru Wall, Ezifit In-Wall, Ezifit Thru Roof, Vogue/Ring Plate



RUN-ON TIMER

4-PIN PLUG SUPPLY WITH PLUG-IN OUTLET

220-240V, single-phase, 50Hz. Fan with 3-pin plug and lead connects directly. Fitted with 4-pin plug and 900mm lead for connection to 4-pin GPO. 6 minute fixed timer.

PART NO.	RUN-ON TIME	MAX. AMPS	TO SUIT FAN SELECTED
VZ6-4PL	6 min (fixed)	5.0	Vogue/RingPlate, Ezifit Thru Wall, Ezifit Thru Roof, TD Silent, Rapid Response, ProVent