



- Double Pole Switching
- Full Rated to 20A
- Complete With Key

Product Specification Data

Revision Date: 15/10/2021

Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	3 x 2.5, 2 x 4.0, 1 x 6.0 mm ²
Frequency	50 Hz
LRV Value	73
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	2-pole switch
Method of operation	Key
Assembly arrangement	Control element
Number of modules (module system)	1
Push button switch	No
Number of rockers	0
Mounting method	Module frame
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	White
Illumination	No
Function lighting	Other
Type of lighting	Not included
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	20 A
Connection type	Screwed terminal

Width of device	25 mm
Height of device	55.5 mm
Depth of device	25 mm
Built-in depth	20.5 mm
Min. depth of built-in installation box	25 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.