BCAB-L CP 17-20 COMBI 407 BK

Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Type	BCAB-L CP 17-20 COMBI 407 BK
WISKA-Order no.	10110231

Describtion:

BC-KIT 2 Includes:
10 x EBFS 17-20/ 2 x COMBI 407/ 10m BCAB-L 17/ 10 x EMUG 20

Technical desciption of components:

EBFS 17-20 - Material number 10106867
Material Conduit fitting polyamide UL94-V0
Material Connection thread polyamide UL94-V0
Material sealing gasket TPU
Protection class IP66, IP68
Temp. range min -40 °C
Temp. range max 100 °C
Operational areas EN 45545 - Railway
NW 17
Thread type M
Ø Connection thread D 20
Lead 1,5
Length screw-in thread L 12 mm
Ø closure VD 32,7 mm
Ø inside 14,8 mm
Key width SW 27 mm
Total length TL 41,5 mm
Type of conduit fitting straight
UL 1696 Yes
Product Color RAL 9005

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice

COMBI 407- Material number 10105601
Material Polypropylene
Material sealing gasket TPE
Temp. range min -30 °C
Temp. range max 100 °C
Temperatures during install. -5 °C - 60 °C
Protection class IP66 / IP67
Glow wire test 750 °C
Voltage 690 V
Rated cross section 4 mm²
Fixing 4 internal openings
Ø cable diameter min 3 mm
Ø cable diameter max 12 mm
External dimensions LxWxH 95 x 95 x 60mm
Type of cable gland M 20 x 1,5, M 25 x 1,5
Product Color RAL 9005

BCAB-L 17 - Material number 10109185

Material	**PA6 UL94-HB**
Temp. range min	**-40 °C**
Temp. range max	**140 °C**
Product Color	**RAL 9005**
NW	**17**
External diameter ED	**21,2 mm**
Ø inside	**16,8 mm**
Profile width A	**3,3 mm**
Width B	**2,3 mm**
Bending radius R	**50 mm**
Wall thickness S	**0,3 mm**
Model	**light**

EMUG 20 - Material number 10061782

Material	**Polyamide, fibre reinforced**
Temp. range min	**-40 °C**
Temp. range max	**100 °C**
Glow wire test	**650 °C**
Thread type	**M**
Ø Connection thread D	**20**
Lead	**1,5**
Key width SW	**27 mm**
Collar diameter (E)	**29 mm**
Total length TL	**5 mm**
Product Color	**RAL 9005**

27.11.2025

Your Contact:
WISKA UK Ltd.
Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain
☎ +44-12-08816062 · 🖷 +44-12-08816708
info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice