

TKE/P 32+/EN LG



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material cable gland	Polyamide
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66
Product Color	RAL 7035
Thread type	M
Ø Connection thread D	32
Lead	1,5
Length screw-in thread L	12 mm
Key width SW	36 mm
Total length TL	42 mm - 51 mm
Glow wire test	750 °C
Type of cable anchorage	A
Install. torques fitting	15 N/m
Install. torques cap nut	4 N/m
Impact category	4
Order no. RAL 7035	10111665
Type	TKE/P 32+/EN LG
Packing unit	1
ETIM-Classification	EC000441

Description:

TKE/P 32+/EN Tails kit 2 x 25mm tails + 1 x 16mm c/w 1 x KRM 32/40

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

WISKA Tail Kits provide a solution to the wiring of Amendment 3 compliant consumer units. Utilising their unique inserts, the Tail kit allows metal tails and earth to be installed through one insert, providing cable retention, preventing eddy currents whilst also maintaining appropriate fire integrity of the board.

28.03.2022

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk