


CUR 818

Plastic Consumer Unit Relocation



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material	Thermoplastic
Protection class	IP65
Temp. range min	-25 °C
Temp. range max	85 °C
Glow wire test	650 °C
Impact resistance	IK07
External dimensions LxWxH	215x200x95mm
Type	CUR 818
Product Color	RAL 7035
Order no. UK	818CUR
Packing unit	1

Description:

Fast self-tapping stainless screws

Terminals

- 2102-1201 - Grey 2 Conductor DIN-rail terminal with Lever and Push-in up to 4mm
- 2102-1204 - Blue 2 Conductor DIN-rail terminal with Lever and Push-in up to 4mm
- 2102-1207 - Green/Yellow 2 Conductor DIN-rail terminal with Lever and Push-in up to 4mm
- 2110-1201 - Grey 2 Conductor DIN-rail terminal with Lever and Push-in up to 16mm
- 2110-1204 - Blue 2 Conductor DIN-rail terminal with Lever and Push-in up to 16mm
- 2110-1207 - Green/Yellow 2 Conductor DIN-rail terminal with Lever and Push-in up to 16mm
- 2110-1292 - Orange Endplate for 2110

13.12.2021

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk