

SHARK 6801 DW

SHARK SIXEIGHT



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|----------------------------|--------------------|
| Material | Polyamide |
| Filling | Silicone |
| Temp. range min | -20 °C |
| Temp. range max | 90 °C |
| Glow wire test | self-extinguishing |
| Protection class | IP68 |
| Voltage | 0,6 kV - 1 kV |
| Type | SHARK 6801 DW |
| UK-Number | SH6801DW |
| WISKA-Order no. | 10108953 |
| Packing unit | 1 |
| ETIM-Classification | EC001169 |

Remarks:

Ampere: 41
Cable Size: (5 core) 2.5 - 6 mm
LxBxH: 190x60x48 mm

Description:

SHARK SIXEIGHT IP 68 rated pre-filled gel insulated joint, including modular bolts and gaskets, cable retention clamp, spring coil and earthing braid.

Additional Info:

Ready to use, re-enterable, 100% watertight, 100% dust-tight, suitable for SWA cables, no mixing or pouring, immediate operation, excellent electrical insulation, good mechanical strength, no expiry date.

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708



info@wiska.co.uk · www.wiska.co.uk

28.04.2025

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk