

Order Code: XCBLC15CTD
15W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Dimmable



Features

- Suitable for general domestic and commercial use
- CCTK [3000K/4000K/6000K] adjustable via simple 3-way selector switch
- Available in 6 sizes
- Available in 6 different outputs
- Phase cut dimming option available
- 3 hours emergency maintained with compatible conversion box
- Up to 100 lumens per Watt efficacy

Construction

- Opal polycarbonate diffuser



Technical Data

Table with 2 columns: General, and values for Luminaire Wattage (W), Weight (kg), and Operating Temperature (ta °C).

Table with 2 columns: Light Output, and values for Lumens (lm) and Efficacy (lm/W).

Table with 2 columns: Electrical, and values for Rated Input Current (A), Power Factor (pf), Input Voltage Range (VAC), Inrush Current Peak (A), Surge Protection (kV), Conductor Size (mm), and Terminal Type.

Table with 2 columns: LED, and values for CCT (K), TRI-COLOUR, CRI, and Macadam Elipses.

Table with 2 columns: Driver, and values for Driver Current (mA) and Forward Voltage (V).

Table with 2 columns: Dimensions, and values for C (mm), Cut Out (mm), and Dia. (mm).

