

Order Code: XCBLC8CTD

8W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Dimmable



Features

- Suitable for general domestic and commercial use
- CCTK [3000K/4000K/6000K] adjustable via simple 3-way selector switch
- Available in 6 sizes
- Available in 6 different outputs
- Phase cut dimming option available
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 88 lumens per Watt efficacy

Construction

- Opal polycarbonate diffuser



Technical Data

General		Dimensions	
Luminaire Wattage (W)	8	C (mm)	26
Weight (kg)	0.12	Cut Out (mm)	100
Operating Temperature (ta °C)	0°C - 25°C	Dia. (mm)	120
Light Output			
Lumens (lm)	700		
Efficacy (lm/W)	88		
Electrical			
Rated Input Current (A)	0.04		
Power Factor (pf)	0.96		
Input Voltage Range (VAC)	198-264		
Inrush Current Peak (A)	1		
Surge Protection (kV)	1		
Conductor Size (mm)	0.75 - 1.5 mm ²		
Terminal Type	PUSH BUTTON 2		
LED			
CCT (K)	TRI-COLOUR		
CRI	80		
Macadam Ellipses	4		
Driver			
Driver Current (mA)	200		
Forward Voltage (V)	27-42		

