

Order Code: XCBT4X1M3
BATTEN X1 CCT [3000K/4000K/6000K] + Wattage Switchable - Emergency



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- CCT [3000K/4000K/6000K] adjustable via simple 3-way selector switch
- Wattage [20 to 36] adjustable via 2-way dip switch

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral emergency option available
- Loop in/out mains connector
- BESA fixings for rear or end cable entry



Technical Data

Table with 2 columns: Parameter, Value. Rows include General (Luminaire Wattage, Weight, Operating Temperature), Light Output (Lumens, Efficacy), LED (CRI, Macadam Elipses), Driver (Driver Current, Forward Voltage), and Emergency (Emergency Lumen Operating, Emergency Wattage).

Table with 2 columns: Parameter, Value. Rows include Electrical (Rated Input Current, Power Factor, Input Voltage Range, Inrush Current Peak, Surge Protection, Conductor Size, Terminal Type).

Order Code: XCBT4X1M3

BATTEN X1 CCT [3000K/4000K/6000K] + Wattage Switchable - Emergency

Dimensions	
A (mm)	1200
B (mm)	55
C (mm)	58
Fix	610

Line Drawing

