

Order Code: XCBT5X1M3
BATTEN X1 CCT [3000K/4000K/6000K] + Wattage Switchable - Emergency



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- CCT [3000K/4000K/6000K] adjustable via simple 3-way selector switch
- Wattage [31 to 57] adjustable via 2-way dip switch

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral emergency option available
- Loop in/out mains connector
- BESA fixings for rear or end cable entry



Technical Data

Table with 2 columns: Parameter, Value. Rows include General (Luminaire Wattage, Weight, Operating Temperature), Light Output (Lumens, Efficacy), LED (CRI, Macadam Ellipses), Driver (Driver Current, Forward Voltage), and Emergency (Emergency Lumen Operating, Emergency Wattage).

Table with 2 columns: Parameter, Value. Rows include Electrical (Rated Input Current, Power Factor, Input Voltage Range, Inrush Current Peak, Surge Protection, Conductor Size, Terminal Type).

Order Code: XCBT5X1M3

BATTEN X1 CCT [3000K/4000K/6000K] + Wattage Switchable - Emergency

Dimensions

|        |      |
|--------|------|
| A (mm) | 1500 |
| B (mm) | 55   |
| C (mm) | 58   |
| Fix    | 610  |

Line Drawing

