

Order Code: XCFRAT5CTPC

5W - Fire Rated Recessed Mini Tilt Dimmable Downlight - CCTK selector [3000K/4000K/6000K] - Polished Chrome



Features

- Compact fire rated tilt downlight with AC on board driver technology
- CCTK adjustable via simple 3-way selector switch
- Fully adjustable tilted lens
- Dimmable as standard
- Convert to larger sized cut outs with the [Conversion Plates](#)
- 30 minute fire rating with Staircraft I-Joist and METAL WEB Joist [[Compatibility Matrix](#)]
- 30, 60 & 90 minute fire rating with solid timber joists
- Up to 90 lumens per Watt efficacy

Construction

- White, Matt White, Satin Nickel or Polished Chrome Finish
- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- Loop in/out mains connections with easy-fit connector
- Integral driver

Technical Data

General	
Luminaire Wattage (W)	5
Weight (kg)	0.19
Operating Temperature (ta °C)	0°C to 25°C
Light Output	
Lumens (lm)	400-500
Efficacy (lm/W)	90
Electrical	
Rated Input Current (A)	0.014
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	5
Surge Protection (kV)	1
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key
LED	
CCT (K)	TRI-COLOUR
CRI	80
Macadam Ellipses	4

Dimensions

C (mm)	67
Cut Out (mm)	65
Dia. (mm)	85

