

Order Code: XCFRAX1W
2700K-6000K + Wattage Selectable - White



Features

- Suitable for domestic applications
- Ideal for retrofit of existing halogen downlight fixtures
- CCT [2700K,3000K,4000K,6000K] adjustable via 4-way selector switch
- Wattage [4W,6W] adjustable via 2-way selector switch
- 30, 60 & 90 minute fire rating with solid timber joists
- 30 minute fire rating with Staircraft I-Joist and METAL WEB Joist [Compatibility Matrix]
- Supplied with white magnetic bezel as standard
- Interchangeable X1 Bezels and X1 Conversion plates [Sold Separately]

Construction

- Easy accessible CCT and Wattage switches beneath magnetic fix bezel for quick and simple adjustment
- Plug and play connections

Installation Notes

Screwless colour-coded terminals for quick & easy installation

Technical Data

Table with 2 columns: Parameter, Value. Rows include General (Luminaire Wattage, Weight, Operating Temperature), Light Output (Lumens, Efficacy), LED (CCT, CRI, Macadam Ellipses), and Driver (Driver Current, Forward Voltage).

Table with 2 columns: Parameter, Value. Rows include Electrical (Rated Input Current, Power Factor, Input Voltage Range, Inrush Current Peak, Surge Protection, Conductor Size, Terminal Type).

**Order Code:** XCFRAX1W  
2700K-6000K + Wattage Selectable - White

Dimensions

|              |    |
|--------------|----|
| B (mm)       | 45 |
| Cut Out (mm) | 70 |
| Dia. (mm)    | 85 |

Line Drawing

