


Order Code: XCLS429CTWD

XCITE LINEAR SUSPENDED CCT XCLS - White - 29W - Dimmable - 3000K/4000K/5000K - Opal diffuser



Features

- Suitable for offices and schools
- Independently switchable up/down modes with adjustable CCT [3000K/4000K/5000K]
- DALI Dimmable as standard
- Complete with adjustable 1.5m wire suspension and 1.8m power feed
- Up to 109 lumens per Watt efficacy

Construction

- Opal polycarbonate diffuser
- Emergency option available
- Extruded aluminium body finished in black or white
- Fitted polycarbonate end caps



Technical Data

General

Luminaire Wattage (W)	29
Weight (kg)	3.76
Operating Temperature (ta °C)	0 to 25

Light Output

Lumens (lm)	3200
Efficacy (lm/W)	109

LED

CRI	91
Macadam Elipses	<5

Driver

Driver Current (mA)	700
Forward Voltage (V)	41.3

Electrical

Rated Input Current (A)	0.13
Power Factor (pf)	0.97
Input Voltage Range (VAC)	220 to 240
Surge Protection (kV)	1
Conductor Size (mm)	0.5 to 2.5
Terminal Type	SLK series 4 to pole grip to wire + 2 to pole grip to wire

Order Code: XCLS429CTWD

XCITE LINEAR SUSPENDED CCT XCLS - White - 29W - Dimmable - 3000K/4000K/5000K - Opal diffuser

Dimensions

A (mm)	1200
B (mm)	45
C (mm)	70
Fix	975

Line Drawing

