

### Order Code: XCNC15NWM3

32W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K



#### Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 144 lumens per Watt efficacy

#### Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

#### Technical Data

General		Electrical	
Luminaire Wattage (W)	32	Rated Input Current (A)	0.1
Weight (kg)	2.24	Power Factor (pf)	0.98
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	198-264
<b>Light Output</b>		Inrush Current Peak (A)	20.02
Lumens (lm)	4300	Conductor Size (mm)	2.5
Efficacy (lm/W)	144	Terminal Type	4 pole piano key
<b>LED</b>		<b>EPREL Sticker</b>	
CCT (K)	4000		
CRI	80		
Macadam Ellipses	3		
<b>Driver</b>			
Driver Current (mA)	700mA		
Forward Voltage (V)	24-42		
<b>Emergency</b>			
Emergency Lumen Operating	160		
Emergency Wattage (W)	1		

**Order Code: XCNC15NWM3**

32W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1560
B (mm)	98
C (mm)	93

Line Drawing

