

Order Code: XCNC25NWM3

65W - 1500mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K



Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 123 lumens per Watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]


Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General	
Luminaire Wattage (W)	65
Weight (kg)	3.31
Operating Temperature (ta °C)	5 to 25
Light Output	
Lumens (lm)	8000
Efficacy (lm/W)	123
LED	
CCT (K)	4000
CRI	80
Macadam Ellipses	3
Driver	
Driver Current (mA)	1400mA
Forward Voltage (V)	24-42
Emergency	
Emergency Lumen Operating	160
Emergency Wattage (W)	1

Electrical	
Rated Input Current (A)	0.27
Power Factor (pf)	0.98
Input Voltage Range (VAC)	198-264
Inrush Current Peak (A)	33.1
Conductor Size (mm)	2.5
Terminal Type	4 pole piano key

EPREL Sticker



Order Code: XCNC25NWM3

65W - 1500mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1560
B (mm)	154
C (mm)	95

Line Drawing

