

Order Code: XCNC6X1M3
1800mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Wattage adjustable via 2-way dip switch [35W/44W/53W/62]
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular emergency pack and microwave sensor's available for quick and easy conversion of a standard fitting
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	35W/44W/53W/62	Rated Input Current (A)	0.17 to 0.29
Weight (kg)	2.81	Power Factor (pf)	0.92 to 0.96
Operating Temperature (ta °C)	+5° to +25°	Input Voltage Range (VAC)	220 to 240
Light Output		Inrush Current Peak (A)	45A
Lumens (lm)	6000 - 10400	Surge Protection (kV)	1
Efficacy (lm/W)	170	Conductor Size (mm)	0.5 to 2.5
LED		Terminal Type	4 pole piano key
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Elipses	8		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	155 to 164Vdc		
Emergency			
Emergency Lumen Operating	327		
Emergency Wattage (W)	2		

Order Code: XCNC6X1M3
1800mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency

Dimensions

A (mm)	1875
B (mm)	95
B (mm)	80
Fix	600

Line Drawing

