

**Order Code: XCSBT555NWM3**

55W - 1500mm Batten - 4000K - 3hrs Maintained Emergency

**Features**

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 119 lumens per Watt efficacy

**Construction**

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Loop in/out mains connector
- Integral emergency option available
- Integral high quality driver and LED module
- BESA fixings for rear or end cable entry



**Technical Data**

**General**

Luminaire Wattage (W)	55
Weight (kg)	1.50
Operating Temperature (ta °C)	5°C to 25°C

**Light Output**

Lumens (lm)	6550
Efficacy (lm/W)	119

**Electrical**

Rated Input Current (A)	0.25
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	13
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	4 pole piano key

**LED**

CCT (K)	4000
CRI	80
Macadam Ellipses	4

**Emergency**

Emergency Lumen Operating	190
Emergency Wattage (W)	1

**Dimensions**

A (mm)	1500
B (mm)	55
C (mm)	58
Fix	610

