

Order Code: XCSF20NW

20W - High Output Slim Floodlight - IP65 - Black - 4000K



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 80 lumens per Watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation

Technical Data

General

Luminaire Wattage (W)	20
Weight (kg)	0.93
Operating Temperature (ta °C)	-20° to 25°

Light Output

Lumens (lm)	1600
Efficacy (lm/W)	80

Electrical

Rated Input Current (A)	0.095
Power Factor (pf)	0.9
Input Voltage Range (VAC)	100-240
Inrush Current Peak (A)	60
Surge Protection (kV)	0.5
Conductor Size (mm)	1.5
Terminal Type	3 pole screw down

LED

CCT (K)	4000
CRI	65
Macadam Ellipses	4

Dimensions

A (mm)	200
B (mm)	150
C (mm)	50

