

Order Code: XCUCL14CT
CABINET LIGHT CC Cabinet/Shaver Lights 14W - 3000K-4000K



Features

- CCT [3000K/4000K] adjustable via simple 2-way selector switch
- Slimline profile for discreet installation
- Up to 114 lumens per Watt efficacy

Construction

- Extruded plastic body
- LED SMD modules array

Technical Data

General	
Luminaire Wattage (W)	14
Weight (kg)	0.21
Operating Temperature (ta °C)	0 to 25
Light Output	
Lumens (lm)	1600
Efficacy (lm/W)	114
LED	
CCT (K)	3000K/4000K
CRI	80
Macadam Ellipses	5
Driver	
Driver Current (mA)	180
Forward Voltage (V)	72

Electrical	
Rated Input Current (A)	0.07
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	5
Surge Protection (kV)	0.5
Conductor Size (mm)	0.5 to 2.5
Terminal Type	2 core flex

Order Code: XCUCL14CT
CABINET LIGHT CC Cabinet/Shaver Lights 14W - 3000K-4000K

Dimensions

A (mm)	857
B (mm)	23
C (mm)	37

Line Drawing

