

Order Code: XCUCL16CT
CABINET LIGHT CC Cabinet/Shaver Lights 16W - 3000K-4000K



Features

- CCT [3000K/4000K] adjustable via simple 2-way selector switch
- Slimline profile for discreet installation
- Up to 125 lumens per Watt efficacy

Construction

- Extruded plastic body
- LED SMD modules array

Technical Data

General		Electrical	
Luminaire Wattage (W)	16	Rated Input Current (A)	0.08
Weight (kg)	0.27	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	5
Lumens (lm)	2000	Surge Protection (kV)	0.5
Efficacy (lm/W)	125	Conductor Size (mm)	0.5 to 2.5
LED		Terminal Type	2 core flex
CCT (K)	3000K/4000K		
CRI	80		
Macadam Ellipses	5		
Driver			
Driver Current (mA)	205		
Forward Voltage (V)	72		

Order Code: XCUCL16CT
CABINET LIGHT CC Cabinet/Shaver Lights 16W - 3000K-4000K

Dimensions

A (mm)	1157
B (mm)	23
C (mm)	37

Line Drawing

