SPEC SHEET - 407552 (HS007)

Zip Hydroboil

Instant on-wall boiling water

Enjoy no waiting time with this convenient, reliable and safe wall-mounted instant boiling water unit. Advanced technology delivers boiling water heated to within 0.5°C of set temperature. Simple to use, it employs an external two-way classic tap with fingertip control for filling cups. The tap also locks on to fill pots hands-free.



MODEL	TANK SIZE (litres)	HEAT UP TIME (INLET 15°C)	HEAT UP TIME (INLET 10°C)	NOMINAL POWER RATING KW	DIMENSIONS W X D X H	FILLED WEIGHT
407552	7.5	23mins	23mins	2.2 kW @ 230V	329mm x 201mm x 586mm	20.5kg

Features and benefits

Convenience

The Hydroboil range delivers reliable boiling water instantly, saving time and helping to increase workplace productivity.

Space saving

Wall-mounted units save much-needed counter-top and under-counter space.

Easy and safe to use

Simple controls and a range of safety features give you complete peace of mind.

Energy efficient

Steam-Heat-Boost technology saves energy by recycling steam to pre-heat incoming cold water – making boiling quicker and less costly.

Wide range

With capacities ranging from 1.5 to 40 litres, there is a model for every situation.

Technical Support Tel. 0345 6 005 005 Email: service@zipindustries.co.uk specify.zipwater.co.uk

Product detail

Specification type

Product code	407552 (HS007)
Product name	HydroBoil HS007 7.5ltr Instant on-wall boiling water heater in white
Case material	Corrosion Resistant White Enamelled Steel
Instant boiling water	Twin chamber
Control	N/A
Service Access Port	Top and bottom

Capacity, weights & dimensions

Capacity	7.5ltrs
Unit dimension (W x D x H)	329mm x 201mm x 586mm
Product weight	20.5kg

Plumbing

Wholesome cold water inlet supply required	Yes
Supply pressure range	0.07 MPa (0.7bar) - 0.5 (5bar)
Inlet pipe	1/2"bsp
Vent pipe	15mm
Vent discharge	Visible tundish or drainage board
Installation	Must comply with current water supply regulations

The minimum water pressure will vary if a limescale filter is installed. Please contact us to discuss your requirements.

Electrical

Nominal power rating kw	2.2 kW @ 230V
Power supply 40L models	Separate 220-240V AC 50Hz ring main rated at 32A isolated by double pole isolation switch
Installation	Must comply with current IEE regulations

Warranty

2 Year on-site parts and labour on site	Terms and conditions apply (visit website for more information)

Technical drawings & dimensions

All dimensions in mm



