



Zip HydroChill HC45

FILTERED: CHILLED

HydroChill HC45T130 under counter chilled water dispensing with heavy duty tap and 3 micron, Zip MicroPurity filtration. With a capacity of 30 litres per hour, and capability for one touch filling of bottles and carafes.



MODEL	TAP STYLE	ULTRA VIOLET	CAPACITY (L/HR)	NOMINAL POWER RATING KW	DIMENSIONS W X D X H
HC45T130	Tap Dispense	N	30 L/hr	.175 kW @ 230V AC	181mm x 343mm x 378mm

Features and benefits

Pure, clean water

Provide pure-tasting water in an instant, thanks to Zip's 3 micron MicroPurity filtration system, which removes impurities and contaminants.

Environmentally responsible

Create a healthier, greener workplace with no need for plastic bottles.

Caters for high volume usage

The HydroChill range has been designed to cater for commercial settings where large volumes of drinking water are required. In fact, the HydroChill Under-Counter HC50 has the capability to provide up to 150 litres of chilled or sparkling water an hour from a single unit.

Consumables and accessories

Serve clean-tasting water in a professional way by using Zip's table-top glass bottles.

Easy to install

Quick and simple to install and use.

Product detail

Specification type

Product code	HC45TI30
Product name	HydroChill HC45 under-counter 30 litre chilled single lever tap
Cooling Technology	Push fed, direct chill reservoir
Refrigerant gas	Natural gas R290



WARNING R290 is a CFC free, environmentally friendly but highly flammable gas. The product should be installed and operated within the instructions in the supplied manual

Capacity, weights & dimensions

Water Functions	Chilled
Capacity (litres per hour)	30 L/hr
Product weight - empty / full	15.6kg / 15.6kg
Unit dimensions (W x D x H) mm	181mm x 343mm x 378mm

Plumbing

Whole cold water inlet supply required	Yes
Water Connection Size	15mmBSP
Inlet pipe	15mm
Supply pressure range	1.03bar (Min) - 8.62bar (Max)
Installation	Must comply with current water supply regulations

The minimum water pressure will vary if a limescale filter is installed. Please contact us to discuss your requirements.

Electrical

Nominal power rating kw	.175 kW @ 230V AC
Power supply option	1x 13amp socket outlet
Installation	Must comply with current IEE regulations

Filtration

Taste & Odour Filtration Kit - available to purchase	93705 - ZIP MicroPurity taste & odour filter HD 3 micron
Sterilising UV filtration at point of dispense	No

Warranty

1 Year on-site parts and labour on site	Terms and conditions apply (see supplied manual)
---	--

Technical drawings & dimensions

All dimensions in mm

